

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS

Red Fir, 12 ins. diam., bears S.48*W., 33 lks. dist.,
marked T 30 S R 4 W S 36 B T C C.

Altitude, 1876 ft.

Cor. to Secs. 30 and 31, T 30 S R 3 W., bears N.1*75'E.,
27.67 chs. as established by W. Thiel. Post and B.T.
standing.

Altitude, 1120 ft.

Land, mountainous, rough and broken.

Soil, poor, 4th rate.

Timber, principally Fir and brush.

Thence

From the established corner to Secs. 23, 24, 25 and 26,
T. 30 S., R. 4 W., as established by Wm. Thiel on
left bank of S. Umpqua river, to-wit:

A quartz rock, with mound of boulders, no marks observed,
from which

An Alder, 6 ins. diam., bears N.55*E., 77 lks. dist.,
marked T 30 S R 4 W S 25 B T.

An Alder, 4 ins. diam., bears N.11 3/4*E., 111 lks.
dist., marked T 30 S R 4 W S 24 B T. (Thiel re-
port of Willow not correct.)

An Alder, 8 ins. diam., bears S.68*W., 152 lks.
dist., marked T 30 S R 4 W S 26 B T. (Thiel,
S.38*W. not correct.)

A B. Oak, 24 ins. diam., bears N.53 1/4*W., 286 lks.
dist., marked T 30 S R 4 W S 23 B T.

Thence

East, between Secs. 24 and 25.

Altitude, 910 ft.

Var. 19*E.

Took a point East on right bank of river, measured base
South 1.00 ch., angle 14 1/2* to point on right bank,
Distance over river 3.86 chs.