

Subdivision of T. 30 S., R. 4 W.

CHAINS

1.50 Left bank of river.
 3.86 Right bank of river.
 15.50 County road to Canyonville.
 37.06 Intersect Tp. line at a point set by W. H. Byars,
 April 27, 1872. Set W. Oak post $4\frac{1}{2}$ ft. long, 4 ins.
 sq., 24 ins. in ground for Cor. to Secs. 24 and 25,
 marked T 30 S R 4 W S 24 NW C C T 30 S R 4 W S 25 SW
 C C, with 4 notches on N. edge and 2 notches on S.
 edge, with mound of rock at base of post, from which
 A B. Oak, 14 ins. in diam., bears N.51*W., 61 lks.
 dist., marked T. 30 S R 4 W C C S 24 B T.
 A Laurel, 6 ins. diam., bears S.74 $\frac{3}{4}$ *W., 25 lks.
 dist., marked T 30 S R 4 W C C S 25 B T.

Altitude, 1300 ft.

Land, hilly and broken.

Soil, sandy, 2d rate.

Timber, Oak and Fir, principally Oak.

Undergrowth, same.

Cor. to Secs. 19 and 30 T 30 S R 3 W bears N.2*00'E.

27.96 chs. as established by W. Thiel. Post and B T.
 standing.

Altitude, 1383 ft.

Land, hilly, rough and broken.

Soil, sandy and rocky, 3d rate.

Timber, Oak and Fir, principally Oak.

Undergrowth, same.

Thence

From established corner to Secs. 13, 14, 23 and 24 T 30 S
 R 4 W as established by W. Thiel, to-wit:

A W. Oak post, 4 ft. long, 4 ins. sq., 24 ins. in the
 ground, marked T 30 S R 4 W S 13 on NE., S 23 on SW.,
 S 14 on NW., and S 24 on SE., 3 notches on S. and
 1 notch on E. edges, from which