

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS

A B. Oak, 9 ins. diam., bears N.70\*E., 19 lks. dist.,  
marked T 30 S R 4 W S 24 B T.

A B. Oak, 20 ins. diam., bears N.4\*E., 41 lks. dist.,  
marked T 30 S R 4 W S 13 B T.

A B. Oak, 9 ins. diam., bears S.55\*W., 19 lks. dist.,  
marked T 30 S R 4 W S 23 B T.

A B. Oak, 10 ins. diam., bears N.61\*W., 36 lks. dist.,  
marked T 30 S R 4 W S 14 B T.

Thence

East, between Secs. 13 and 24, T 30 S R 4 W.

Var. 18\*45'E.

Altitude, 1045 ft.

7.60 Stream, 3 lks. wide, course S.

29.50 Top of ridge, course S.

Altitude, 1150 ft.

37.50 Intersect Township line 39 lks. N. of corner formerly  
set by W.H. Byars. Set B. Oak post, 4½ ft. long,  
4 ins. sq., 24 ins. in ground, for Cor. to Secs. 13 and  
24. T 30 S R 4 W, marked S 13 NW. C C. 3 notches on N.  
edge, S 24 SW C.C. 3 notches on S. edge, from which  
A W. Oak, 4 ins. diam., bears N.10\*W. 50 lks. dist.,  
marked T 30 S R 4 W S 13 C.C. B T.  
A Fir, 8 ins. diam., bears S 60\*W., 53 lks. dist.,  
marked T 30 S R 4 W S 24 C.C. B T.

Altitude, 1120 ft.

Land, hilly, rough and broken.

Soil, sandy and rocky, 2d rate.

Timber, Oak and Fir, principally Oak.

Undergrowth, Fir and Oak.

Corner to Secs. 18 and 19 T 30 S R 3 W bears N.2\*E.,  
27.09 chs. dist. The established corner as made by  
W. Thiel. Post and B T standing.

Altitude, 1320 ft.

Thence

From the established corner to Secs. 11, 12, 13 and 14,