

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS 5.45	Top of ridge, course E. and W. Altitude, 2475 feet.
22.31	To corner, as established by W. Thiel.
	Sept. 17, 1891.
	Thence From established Cor. of Secs. 1, 2, 11 and 12, T. 30 S., R. 4 W., as established by Wm. Thiel, to-wit: A Fir post, 4 ins. square, marked T 30 S R 4 W S 1 NE. S 2 NW., S 11 SW., 5 notches on S. edge, S 12 SE., 1 notch on E. edge, from which A W. Fir, 8 ins. diam., bears N.67*E., 26 lks. dist., marked T 30 S R 4 W S 1 B T. A R. Fir, 36 ins. diam., bears S.6*E., 51 lks. dist., marked T 30 S R 4 W S 12 B T. A R. Fir, 24 ins. diam., bears S.82*W., 52 lks. dist., marked T 30 S R 4 W S 11 B T. A R. Fir, 14 ins. diam., bears N.85*W., 20 lks. dist., marked T 30 S R 4 W S 2 B T.
	Thence East, between Secs. 1 and 12, T. 30 S., R. 4 W. Altitude, 960 feet. Var. 18*45'E.
2.00	Enter point of hill.
7.50	Top of ridge. Altitude, 1200 feet.
15.00	Stream, 3 lks. wide, course NW. Altitude, 1030 Ft., begin to ascend mountain.
29.50	Top of ridge, course N. and S. Altitude, 1510 feet. Begin to descend.
38.31	Intersect Tp. line 25 lks. S. of Cor., set by W. H. Byars. Set Dogwood post, 4½ ft. long, 4 ins. square, 24 ins. in ground, for Cor. to Secs. 1 and 12, T. 30 S., R. 4 W., marked T 30 S R 4 W S 1 C C on NW., 1 notch on N. edge, S 12 C C on SW., 5 notches on S. edge, from which