

Subdivisions of T. 30 S., R. 4 W.

CHAINS

A R. Fir, 16 ins. diam., bears N.29\*W., 21 lks. dist.,  
marked T 30 S R 4 W S 1 C C B T.

A R. Fir, 10 ins. diam., bears S.80\*W., 17 lks. dist.,  
marked T 30 S R 4 W S 12 C C B T.

Land, hilly, rough and broken.

Soil, sandy and rocky, 3d rate.

Timber, Fir.

Undergrowth, same.

Altitude, 1040 feet.

Cor. to Secs. 6 and 7, T. 30 S., R. 3 W., bears N.2\*E.,  
12.70 chs.

5.00 Creek bottom, E. and W.

6.50 Day's Creek, 25 lks. wide, course NW.

12.70 To rock Cor., Red Jasper, the established corner as set  
by Wm. Thiel for Secs. 6 and 7, T. 30 S., R. 3 W.  
Sept. 17, 1891.

Subdivisional lines of T. 30 S., R. 4 W.,  
as surveyed by Wm. M. Bushey, Deputy Surveyor,  
under Contract No. 620, dated June 17, 1893.

I begin at the corner to Secs. 22, 23, 26 and 27, which  
is post, 4 ins. square, firmly set. marked T 30 S S 23  
on NE., R 4 W S 26 on SE., S 27 on SW., and S 22 on  
NW. faces, with 2 notches on E. and S. edges, from which

A Fir, 36 ins. diam., bears N.24\*E., 26 lks. dist.,  
marked T 30 S R 4 W S 23 B T.

A Fir, 24 ins. diam., bears S.1\*E., 102 lks. dist.,  
marked T 30 S R 4 W S 26 B T.

A Fir, 30 ins. diam., bears S.79\*W., 44 lks. dist.,  
marked T 30 S R 4 W S 27 B T.

A Fir, 36 ins. diam., bears N.29\*W., 76 lks. dist.,  
marked T 30 S R 4 W S 22 B T.

These trees are all marked in the bark, and the marks  
are getting dim. I mark them in the wood as follows: