

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R. 4 W.

CHAINS		
	A Fir, 36 ins. diam., bears N.24*E., 26 lks. dist., marked T 30 S R 4 W S 23 B T.	
	A Fir, 24 ins. diam., bears S.1*E., 102 lks. dist., marked T 30 S R 4 W S 26 B T.	
	A Fir, 30 ins. diam., bears S.79*W., 44 lks. dist., marked T 30 S R 4 W S 27 B T.	
	A Fir, 36 ins. diam., bears N.29*W., 76 lks. dist., marked T 30 S R 4 W S 22 B T.	
	S.0*1'W., between Secs. 26 and 27.	
	Var. 18 3/4*E/	
	Ascend.	+500
19.43	A spring branch, 1 lk. wide, course N.25*W.	
36.25	Top of ridge, course NW. and SE. Descend.	-40
39.95	A ravine, course NW. and SE., Ascend.	+125
40.00	A Fir, 20 ins. diam., which I mark $\frac{1}{2}$ S on W. face for $\frac{1}{2}$ Sec. Cor., from which	
	A Fir, 30 ins. diam., bears N.47 $\frac{1}{2}$ *E., 14 $\frac{1}{2}$ lks. dist., marked $\frac{1}{2}$ S B T.	
	A Fir, 24 ins. diam., bears N. $\frac{1}{2}$ *W., 29 $\frac{1}{2}$ lks. dist., marked $\frac{1}{2}$ S B T.	
52.25	Top of ridge, course N.80*E. and S.80*W.	
52.50	Trail, course N.80*E., and S.80*W.; descend.	-300
78.10	A stream, 3 lks. wide, course SE., ascend.	+50
80.00	Set a stone 14x12x4 ins., 10 ins. in the ground for Cor. to Secs. 26, 27, 34 and 35, marked with 2 notches on E. and 1 notch on S. edges, from which	
	A Fir, 34 ins. diam., bears N.57 3/4*E., 69 lks. dist., marked T 30 S R 4 W S 26 B T.	
	A Fir, 36 ins. diam., bears S.52 3/4*E., 34 $\frac{1}{2}$ lks. dist., marked T 30 S R 4 W S 35 B T.	
	A Chinquapin, 12 ins. diam., bears S.71 $\frac{1}{4}$ *W., 91 $\frac{1}{2}$ lks. dist., marked T 30 S R 4 W S 34 B T.	
	A Maple, 16 ins. diam., bears N.44 $\frac{1}{2}$ *W., 75 lks.	