

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R. 4 W.

CHAINS 35.00	Top of ridge, course E. and W., descend.	-125
35.75	Leave windfall.	
40.00	Set a quartz stone 12x12x10 ins., 8 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which A Fir, 26 ins. diam., bears N.42 $\frac{1}{2}$ *E., 11 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 11 ins. diam., bears N.56*W., 10 lks. dist., marked $\frac{1}{4}$ S B T.	
44.75	Intersect the South bdy. of the Tp., 6.00 chs. West of the Cor. to Secs. 3, 4, 33 and 34 and set temp. post. As this closing is not within the prescribed limits I begin at the established Cor. to Secs. 2, 3, 34 and 35, Thence I run West, on a blank line between Secs. 3 and 34. Var. 19*E. Ascend.	+150
8.75	Descend	-50
20.25	A ravine, course SW. and NE. Ascend.	+900
33.60	A gulch, course SW. and NE.	
39.15	To a point 17 lks. South of the $\frac{1}{4}$ Sec. Cor., which is a post 3 ins. square, firmly set, marked $\frac{1}{4}$ S on N. face, from which A Fir, 42 ins. diam., bears S.5*E., 4 lks. dist., marked $\frac{1}{4}$ S B T. A Cedar, 12 ins. diam., bears N.27*E., 9 lks. dist., marked $\frac{1}{4}$ S B T.	
57.50	Top of ridge, course N. and S. Descend.	-900
77.96	To a point 13 lks. North of the Cor. to Secs. 3, 4, 33 and 34, which is a Fir tree 12 ins. diam., marked T 30 S S 34 on NE., R 4 W S 3 on SE., T 31 S S 4 on SW., and S 33 on NW. faces, with 3 notches on E. and W. edges; from which A Fir, 33 ins. diam., bears N.55 $\frac{1}{2}$ *E., 64 lks. dist., marked T 30 S R 4 W S 34 B T.	