

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS		
	<p>$\frac{1}{2}$ S on W. face; from which</p> <p>A Fir, 36 ins. diam., bears N.85*E., 16 lks. dist., marked $\frac{1}{2}$ S B T.</p> <p>A Fir, 24 ins. diam., bears S.84*W., 53 lks. dist., marked $\frac{1}{2}$ S B T.</p> <p>Thence I run</p> <p>S.0*2'W., between Secs. 28 and 29.</p> <p style="text-align: right;">Var. 19$\frac{1}{2}$*E.</p>	
	Ascend.	+60
1.00	Enter dense windfall.	
5.00	Descend.	-100
11.80	A stream, 2 lks. wide, course West, ascend.	+75
15.25	Top of ridge, course E. and W. Descend.	-60
18.30	A ravine, course E. and W. Ascend.	+50
22.05	Top of ridge, course E. and W. Descend.	-60
26.45	A ravine, course E. and W. Ascend.	+60
28.85	Top of ridge, course E. and W. Descend.	-125
34.50	A stream, 1 lk. wide, course N.80*W. Ascend.	+75.
40.00	Set a stone 16x14x6 ins., 12 ins. in the ground, for Cor. to Secs. 28, 29, 32 and 33, marked with 4 notches on E. and 1 notch on S. edges; from which	
	<p>A Fir, 36 ins. diam., bears N.79*E., 136 lks. dist., marked T 30 S R 4 W S 28 B T.</p> <p>A Fir, 30 ins. diam., bears S.74$\frac{1}{2}$*E., 163 lks. dist., marked T 30 S R 4 W S 33 B T.</p> <p>A Fir, 40 ins. diam., bears S.89*W., 84$\frac{1}{2}$ lks. dist., marked T 30 S R 4 W S 32 B T.</p> <p>A Fir, 26 ins. diam., bears N.68$\frac{1}{4}$*W., 70 lks. dist., marked T 30 S R 4 W S 29 B T.</p>	
	Land, mountainous. 40.00 chs.	
	Soil, 3d rate.	
	Heavily timbered with Fir, Laurel and Maple. 12 chs.	
	Undergrowth, Vine-maple, Laurel, Arrow-wood, Hazel,	