

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R. 4 W.

CHAINS		Var. 19*E.
	S.0*2'W., on a true line between Secs. 32 and 33.	
	Ascend.	+60
3.50	Top of spur, course E. and W. Descend.	-600
12.49	A stream, 2 lks. wide, course, N.75*W.	
	Ascend.	+250
25.25	Top of spur, course E. and W.	
	Descend.	-100
34.00	A ravine, course E. and W. Ascend.	+40
36.00	Descend.	-60
38.50	A ravine, course E. and W. Ascend.	+100
40.00	Set a stone 14x12x12 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which A Fir, 12 ins. diam., bears S.54 $\frac{1}{2}$ *E., 35 lks. dist., marked $\frac{1}{4}$ S B T. A Maple, 10 ins. diam., bears N.30 $\frac{1}{2}$ *W., 2 lks. dist., marked $\frac{1}{4}$ S B T.	
43.00	Top of ridge, course E. and W. Descend.	-40
47.30	Intersect the South Bdy. of the Tp. 7.50 chs. West of the Cor. to Secs. 4, 5, 32 and 33, which is, a Laurel tree, 8 ins. diam., marked T 30 S S 33 on NE., R 4 W S 4 on SE., T 31 S S 5 on SW., and S 32 on NW. faces, with 4 notches on E. and 2 notches on W. faces; from which, A Maple, 5 ins. diam., bears N.6*E., 22 lks. dist, marked T 30 S R 4 W S 33 B T. A Laurel, 9 ins. diam., bears S.78*E., 23 lks. dist., marked T 31 S R 4 W S 4 B T. A Fir, 36 ins. diam., bears S.73*W., 28 lks. dist., marked T 31 S R 4 W S 5 B T. A Laurel, 6 ins. diam., bears N.60 $\frac{1}{2}$ *W., 28 lks. dist., marked T 30 S R 4 W S 32 B T.	
	As this closing is not within the prescribed limits, I go to the old Cor. established for Secs. 3, 4, 33 and 34.	