

County Surveyor's Record, Douglas County, Oregon



West bdy. of T. 30 S., R. 5 W.

CHAINS	<p>A laurel, 12 ins. diam., bears N.70*E. 27 lks. dist.  A laurel, 12 ins. diam., bears S.75*E. 55 lks. dist.  A laurel, 10 ins. diam., bears N.45*W. 75 lks. dist.  A R fir, 15 ins. diam., bears S.70*W. 57 lks. dist.</p> <p>Second rate, soil.  Hilly, land.  Timber, oak, fir.  Undergrowth, oak &amp; laurel.</p>	
	<p>South bdy. of T. 30 S., R. 5 W. Same deputy and contract.</p>	
	<p style="text-align: center;">Va.17*45'E.</p> <p>East, on random line on the South boundary of Secs. 31, 32, 33, 34, 35 &amp; 36. Setting temp. mile &amp; half mile posts.</p>	
482.20	<p>Intersected East boundary 3.78 chs.</p>	
	<p>South, of cor. of Tps. 30 &amp; 31. on range line between ranges 4 &amp; 5.</p> <p>The correction will be 63 lks. to the mile.</p>	
	<p style="text-align: center;">Va.18*40'E.</p>	
	<p>S.89*33'W, on true Southern boundary of sec. 36.</p> <p>Began to descend mountain.</p>	
40.00	<p>Set <math>\frac{1}{4}</math> sec. post at proper distance, from which,</p>	-150
	<p>A laurel, 4 ins. diam., bears N.85*W. 11 lks. dist.</p>	
	<p>A laurel, 5 ins. diam., bears S.35*W. 9 lks. dist.</p>	
80.00	<p>Set a post at proper distance, for cor. of secs. 1, 2,</p>	-100
	<p>35 &amp; 36, from which,</p>	
	<p>A R fir, 15 ins. diam., bears S.20*W. 14 lks. dist.</p>	
	<p>A R fir, 6 ins. diam., bears S.30*E. 12 lks. dist.</p>	
	<p>A R fir, 36 ins. diam., bears N.70*W. 30 lks. dist.</p>	
	<p>A laurel, 8 ins. diam., bears N.5*E. 23 lks. dist.</p>	
	<p>Third rate, soil, whole length of line run down West</p>	
	<p>slope of mountain.</p>	
	<p>Timber, fir, laurel.</p>	
	<p>Undergrowth, laurel.</p>	