

Re-survey of Exterior lines of T. 31 S., R. 5 W.
North Bdy.

CHAINS

Thence from the corner to T. 30 & 31 S R 4 & 5 West,

I run,

West, on a random line on the North boundary of T. 31
 S., R. 5 W.

Va.19°E.

I set temp. $\frac{1}{4}$ sec. and section corners at 40 and 80 chs.
 and at 3 miles 9 chains and 61 lks. I intersected lines
 between secs. 3 & 4. 152 lks. South of the cor. to sec.
 3 and 4, 33 and 34. Which is a fir post firmly set in
 the ground and properly marked, T 30 S R 5 W S 34 on
 the NE face, S 33 on the NW face, T 31 S S 3 on the SE
 face, and S 4 on the SW face, also 3 notches on E and
 W angles of same and from which,

A fir, 12 ins. diam., bears N.24°E, 10 lks. dist.
 marked T 30 S R 5 W S 34 B T.

A fir, 16 ins. diam., bears S.82°E, 13 lks. dist.
 marked T 31 S R 5 W S 3 B T.

A fir, 20 ins. diam., bears S.38°W, 20 lks. dist.
 marked T 31 S R 5 W S 4 B T.

A fir, 6 ins. diam., bears N.83°W, 18 lks. dist.
 marked T 30 S R 5 W S 33 B T.

I find the departure to be 50- $\frac{2}{3}$ lks. per mile and
 the true course to be.

August 18 & 29, 1882

S.89°38'E, on a true line.

Beginning at the established corner to Sections 3,4, 33
 and 34.

I run.

S.89°38'E, on a true line along the North bdy of Sec. 3.

Va.19°E.

- 7.00 A creek, 1 lk. wide course North, steep ascent.
- 16.50 Top of high spur course North thence along steep North
 mountain slope.
- 20.00 A high spur course NE. Steep descent.
- 49.61 Set a stone 24x6x6 ins, 12 ins. in the ground for the