

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 5 W.

CHAINS

July 19, 1896.

82.70 Intersect N. bdy of township, 532 lks. E. of cor. to secs. 35 and 36 of T. 29 S., R. 5 W., as re-established and described by me.

Set a basalt stone, 14x10x6 ins. 10 ins. in the ground for closing cor of secs. 1 and 2, marked C C on S; with 1 groove on E. and 5 grooves on W. faces, from which,

A B oak, 10 ins. diam, bears S.4*W, 108 lks. dist. marked T 30 S R 5 W S 2 B T.

No other trees within limits, raised a mound of stone 2 ft. base, 1½ ft. high, S. of cor. This cor. stands on NW slope in burnt laurel and oak underbrush.

Thence I run,

S.0*1'E, on a true line bet. secs. 1 and 2.

Very steep ascent through burnt laurel and oak underbrush.

1.70 A trail, bears E & W, 50 ft. above cor.

Begin less steep ascent of W. slope.

3.00 Entered green heavy undergrowth of laurels, oaks and firs.

26.50 Top of ridge, bears NW and SE., 600 ft. above cor., begin descent of SW. slope covered by a dense undergrowth of poison oak.

A house bears S.27*W, about 40. chains dist.

32.00 Change from SW slope to W. slope of ridge.

42.70 Set a basaltstone, 12x7x6 ins. 8 ins. in the ground, for ¼ sec. cor., marked ¼ on W face, from which,

A B oak, 8 ins. diam., bears S.12-1/2*W, 220 lks. dist, marked ¼ S B T.

A B oak, 24 ins. diam., bears S.12½*E, 195 lks. dist. marked ¼ S B T.

A cold spring is 18 lks. NE from the SW., bearing tree, Along the W. slope through oak timber; slightly ascending ¼ sec. cor. is 200 ft. below top of ridge.