

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 5 W.

CHAINS	
	through heavy fir timber, 500 ft. below top of spur.
76.00	Top of spur, bears SW and NE, begin moderate descent of W. slope.
80.00	A B oak, 5 ins. diam., for cor. of secs., 3, 4, 9 & 10, I marked, T 30 S S 3 on NE., R 5 W S 10 on SE., S 9 on SW., S 4 on NW sides, with 5 notches on S. and 3 notches on E. sides; from which,
	A B oak, 6 ins. diam., bears N.45°E, 10 lks. dist., marked T 30 S R 5 W S 3 B T.
	A B oak, 5 ins. diam., bears S.65°E, 17 lks. dist. marked T 30 S R 5 W S 10 B T.
	A B oak, 8 ins. diam., bears S.22½°W, 41 lks. dist. marked T 30 S R 5 W S 9 B T.
	A B oak, 4 ins. diam., bears N.28°W, 14 lks. dist. marked T 30 S R 5 W S 4 B T.
	Land, mountainous.
	Soil, gravelly, 3rd. rate.
	Timber, fir, oak, laurel & pine.
	Dense undergrowth of small firs, hazel, arrow-wood.
	Mountainous land. 80.00 chs.
	At the cor. os secs. 3, 4, 9 and 10.
	Thence I run
	S.89°50'E, on a random line bet. secs. 3 & 10.
40.00	Set temp. ¼ sec. cor.
	July 23, 1896.
80.36	Intersect N. and S. line 46 lks. N. of cor. of secs. 2, 3, 10 & 11.
	Thence I run
	N.89°30'W, on a true line bet. secs. 3 and 10.
	Along the S. slope near top of ridge through scattering oak timber.
8.50	Begin descent of W. slope.
17.75	A dry branch, course S. 450 ft. below sec. cor., begin ascent.