

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 5 W.

CHAINS

begin descent of W. slope.

32.00 Foot of descent, 80 ft. below ridge, begin ascent.

34.50 Top of spur, bears E and W. 60 ft. above foot of descent.
Begin descent.

40.00 Set a yellow fir post, 3 ft. long, 3 ins. sq. 24 ins.

in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face,
from which,

A fir, 12 ins. diam., bears S.45*E, 9 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 10 ins. diam., bears N.45*W, 33 lks. dist.,
marked $\frac{1}{4}$ S B T.

At the $\frac{1}{4}$ sec. cor. bet. secs. 3 & 4.

Keep on descending.

44.50 A trail to Day's creek, bears E and W. 160 ft. below
top of spur, begin ascent.

51.50 Top of dividing ridge, 80 ft. above trail, bears N.10*W
and S.10*E.

52.50 Needle shows a declination of 18*35'E.

Enter small fir timber, and begin descent of N. slope.

67.80 A dry gulch, course NE, begin ascent of E. slope, 175
ft. below top of divide.

80.00 Top of spur, bears E and W., 60 ft. above gulch.

82.59 Intersect N. bdy of the Tp. 695 lks. E. of cor to secs.
3, 4, 33 and 34, which is an oak post, 20 ins. above
ground marked and witnessed as described by the
surveyor general.

I set a laurel post, 3 ft. long 4 ins. sq. 24 ins. in
the ground for closing cor. of secs. 3 and 4, marked
C C T 30 S R 5 W on S., S 3 on E., and S 4 on W faces;
with 3 grooves on E., and W. faces, from which,

A laurel, 16 ins. diam., bears S.55*W, 53 lks. dist.
marked T 30 S R 5 W S 4 B T.

A fir, 36 ins. diam., bears S.44*E, 83 lks. dist.
marked T 30 S R 5 W S 3 B T.

As a large amount of dead timber is lying here, I added
another B T.