

County Surveyor's Record, Douglas County, Oregon

7229

South Boundary T. 30 S., R. 7W., W. M.  
 as surveyed by W. H. Byars, Deputy Surveyor  
 under contract No. 152 dated June 3, 1871.

CHAINS		
	Begin at the post the established corner to Tps. 30 and 31 S., R's. 6 and 7 W.	
	Two of the Witness trees standing	
	A laurel, 18 ins. diam., bears NE.	
	A laurel, 14 ins. diam., bears SW.	
	I run West along South boundary of sec. 36.	
	Va. 17*45'E.	
40.00	Set $\frac{1}{4}$ sec. post, from which	+300
	A laurel, 6 ins. diam., bears N.20*E., 26 lks. dist.	
	A live oak, 12 ins. diam., bears S.65*W., 53 lks. dist.	
42.50	Top of perpendicular precipice 200 ft. high	
44.50	Foot of rocky bluff.	-50
48.50	Cow creek, 75 lks. wide, course NE.	-100
72.00	Cow creek, 150 lks. wide, course SE.	-100
79.25	A creek, 2 lks. wide, course N.	-100
80.00	Set post corner to secs. 1, 2, 35 and 36, from which	
	An alder, 10 ins. diam., bears N.60*E., 125 lks. dist.	
	An alder, 8 ins. diam., bears S.55*E., 66 lks. dist.	
	A W. oak, 18 ins. diam., bears S.30*W., 37 lks. dist.	
	A B. oak, 16 ins. diam., bears N.55*W., 133 lks. dist.	
	Land 2nd. rate.	
	Timber, fir, pine, oak, and laurel, 2nd. rate.	
	May 6, 1872.	
	West, along the South boundary of sec. 35.	
	Va. 21*E.	
40.00	Set $\frac{1}{4}$ sec. post, from which	+900
	A W. pine, 30 ins. diam., bears N.38*E., dist. 26 lks.	
	A S. pine, 48 ins. diam., bears S.72*E., dist. 80 lks.	
52.50	Top of ridge, course N and S.	+1000
80.00	Set post corner to secs. 2, 3, 34 and 35 from which	+300
	A pine, 18 ins. diam., bears N.63*E., 212 lks. dist.	
	A pine, 12 ins. diam., bears S.82*E., 139 lks. dist.	
	A pine, 15 ins. diam., bears S.85*W., 30 lks. dist.	
	A pine, 24 ins. diam., bears N.60*W., 292 lks. dist.	