

West Boundary of T. 30 S., R. 7 W., W. M.
 as surveyed by William H. Byars, Deputy Surveyor
 under contract No. 450, dated July 28, 1882.

CHAINS

I begin at the established cor. to Tps, 30 and 31
 So. Rgs. 7 and 8 W. which is a Live Oak post, 4
 ins. sq. firmly set in the ground and marked
 T. 30 S., R. 7 W. S. 31 on the NE face.
 T. 31 S., S. 6 on the SE face.
 R. 8 W. S 1 on the SW face.
 S. 36 on the NW face and from which
 A Laurel, 6 ins. diam., bears N10*E., 35 lks. dist.
 Marked T. 31 S., R. 7 W S.31., B. T.
 A Live Oak, 6 ins diam., bears S.40*W., 43 lks. dist.
 Marked T. 31 S., R. 8 W S. 1., B. T.
 A Live Oak, 5 ins. diam., bears S.70*E., 32 lks. dist.
 Marked T. 31 S., R. 7 W S. 6., B. T.
 A Live Oak, 5 ins. diam., bears N.70*W., 15 lks. dist.
 Marked T. 30 S., R. 8 W S. 36., B. T.

Thence I run N. between secs. 31 and 36.

Va. 18* 45' E.

- 00.27 Ascend perpendicular bluff 50 ft. high.
- 3.00 Top pf spur, course E. Descend along E. slope.
- 28.70 A creek one lks. wide, course E.
- 31.00 A creek, 12 lks. wide, course S.20*E. (Table creek)
- 35.50 Same creek, course S.20*W.
- 40.00 Set a stone 16 x 14 x 12 ins. in the ground for the $\frac{1}{4}$
 sec. cor. marked $\frac{1}{4}$ on the W. side from which
 A Yew, 10 ins. diam., bears S.30*E., 50 lks. dist.
 Marked $\frac{1}{4}$ S., B. T.
 A Maple, 5 ins. diam., bears W., 36 lks. dist.
 Marked $\frac{1}{4}$ S. B. T.
- 42.00 Same creek, course S.20*E. Steep ascent.
- 80.00 Set a stone 14 x 12 x 5 ins. for the cor. to secs. 25,
 30, 31 and 35, marked with one notch on the S. and
 five notches on the N. angles and from which