

County Surveyor's Record, Douglas County, Oregon

Subdivisions T 30 S., R 7 W., W. 1/2 N.

CHAINS	<p>A Laurel 8 ins. diam., bears S.58*W., 59 lks. dist. Marked T 30 S R 7 W S 10 B. T.</p> <p>A Fir, 30 ins. diam., bears N.64*W., 19 lks. dist. marked T 30 S R 7 W S 3 B. T.</p> <p>Thence a run S 86* 58' W. on true line between secs. 3 and 10.</p> <p style="text-align: right;">va. 21*E.</p>
42.11	<p>Set Cedar post, 3 ft. long, 3 ins. sq. 18 ins. in the ground for 1/4 sec. cor. marked 1/4 S. on N. face from which</p> <p>A Fir, 36 ins. diam., bears N.42*E., 25 lks. dist. Marked 1/4 S. B. T</p> <p>A Fir, 16 ins. diam., bears S.26*E., 51 lks. dist. Marked 1/4 S. B. T.</p>
84.22	<p>The cor. to secs. 3, 4, 9 and 10.</p> <p>Land mountainous and densely covered with forests of fir, Pine, Cedar, and Laurel timber.</p> <p>Soil, 3rd. rate.</p> <p style="text-align: right;">October 5, 1882.</p>
	<p>North on random line between secs. 3 and 4. va. 19* 30'E. Along W. slope of ridge.</p>
16.00	<p>Very steep descent.</p>
39.00	<p>Hunter's creek 40 lks. w. course w.</p>
40.00	<p>Set temp 1/4 sec. cor.</p>
46.88	<p>Ascend bluff, Thence up steep ascent.</p>
57.50	<p>Top of hill. thence along W. slope.</p>
78.45	<p>Intersect Tp. line 266 lks. W. of the cor. to secs. 3, 4, 33 and 34, which is a pine post, 4 ins. sq. firmly set in the ground and marked</p> <p>T 29 S R 7 W S 34 on NE., T 30 S S 3 on SE. S 4 on SW and S 33 on NW faces with 3 notches on E and W edges, from which</p>