

County Surveyor's Record, Douglas County, Oregon

Subdivisions T 30 S R 7 W W. M.

CHAINS

T 30 S R 7 W S 16 on NE, S 21 on S E., S 20 on SW.
S 17 on NW faces with 3 notches on S and 4 notches on
E edges from which

A Laurel, 7 ins. diam, bears N.78*E., 11 lks. dist.

Marked T 30 S R 7 W S 16 B. T.

A Laurel, 7 ins. diam., bears S.14*E., 23 lks. dist.

Marked T 30 S R 7 W S 21 B. T.

A Laurel, 18 ins. diam., bears S.41*W., 10 lks. dist.

Marked T 30 S R 7 W S 21 B. T.

A Fir, 15 ins. diam., bears N.10*W., 45 lks. dist.

Marked T 30 S R 7 W S 17 B. T.

Land mountainous.

Soil 3rd. rate.

Densely covered with forests of Fir, Cedar, Laurel timber.

East on a random line between secs. 16 and 21.

Va 19*E.

Begin steep descent.

23.54 Descend perpendicular bluff 60 ft. high.

36.00 Spur, course SE. Descend.

40.00 Set temp $\frac{1}{4}$ sec. cor.

47.25 Creek 2 lks. W, course S. Ascend.

65.50 Top of spur, course S.60*E. Descend.

77.60 Creek 3 lks. W, course S.

80.00 Intersect N and S line 68 lks. S. of cor. to Secs.

15, 16, 21 and 22, which is a post, 4 ins. sq. firmly
set in the ground and properly marked and from which

A Fir, 6 ins. diam., bears N.15*E., 26 lks. dist.

Marked T 30 S R 7 W S 15 B. T.

A Fir, 10 ins. diam., bears S.52*E., 54 lks. dist.

Marked T 30 S R 7 W S 22 B. T.

A Fir, 10 ins. diam., bears S.38*W., 40 lks. dist.

Marked T 30 S R 7 W S 21 B. T.