

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T 30 S R 7 W W. M.

CHAINS 77.16	<p>The cor. to secs. 4, 5, 8 and 9.</p> <p>Land mountainous.</p> <p>Soil 3rd. rate and densely covered with forests of fir, Pine, Laurel, Oak and Cedar.</p> <p style="text-align: right;">October 11, 1882.</p>
17.08	<p>It being impracticable to extend a line N from the cor. to secs. 5, 6, 31 and 32 by reason of immense bluffs of rock, I begin at the cor. to secs. 28, 29, 32 and 33 and run W on a true line between secs. 29 and 32.</p> <p style="text-align: right;">Va 29*E.</p> <p>Steep descent.</p> <p>Creek 2 lks. wide, course S.</p> <p>Begin steep ascent.</p>
36.50	<p>Ascend bluff 60 ft. high, course N and S.</p>
40.00	<p>Set a fir post, 3 ft. high 3 ins. sq. 18. ins. in the ground for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ S on N face from which</p> <p style="padding-left: 40px;">A Pine, 24 ins. diam., bears S.20*W., 25 lks. dist. Marked $\frac{1}{4}$ S B. T.</p> <p style="padding-left: 40px;">A Fir, 14 ins. diam., bears N.54*E., 22 lks. dist. Marked $\frac{1}{4}$ S B. T.</p>
80.00	<p>Thence along S slope of mt. very rocky and broken.</p> <p>set a stone 16 x 12 x 6 ins. 10 ins. in the ground for the cor. to secs. 29, 30, 31 and 32, marked with 1 notch on the S and 5 notches on the E edges from which</p> <p style="padding-left: 40px;">Live Oak, 6 ins. diam., bears N.60*E., 17 lks. dist. Marked T 30 S R 7 W S 29 B. T.</p> <p style="padding-left: 40px;">Live Oak, 6 ins. diam., bears S.59*E., 26 lks. dist. Marked T 30 S R 7 W S 32 B. T.</p> <p style="padding-left: 40px;">Laurel, 6 ins. diam., bears S.12*W., 87 lks. dist. Marked T 30 S R 7 W S 31 B. T.</p> <p style="padding-left: 40px;">Live Oak, 5 ins. diam., bears N.74*W., 20 lks. dist. marked T 30 S R 7 W S 30 B. T.</p>