

County Surveyor's Record, Douglas County, Oregon

Retracement portion West Bdy T 30 S R 7 W

CHAINS

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Tps. 30 and 31 S. Rs. 7 and 8 W., with brass cap marked

T30S
R8W | R7W
S36 | S31
S1 | S6
T31S
1918

Fnd. O.K.
By H. JOHNSTONE
DEC. 1981 M 89-79

from which

A madrona, 10 ins. diam., bears N.36°E., 34 lks. dist. marked T 30 S R 7 W S 31 B T (Old B.T.)

A live oak, 8 ins. diam., bears S.75°E., 41 lks. dist. marked T 31 S R 7 W S 6 B T (Old B.T.)

A fir, 30 ins. diam., bears S.78°W., 67 lks. dist. marked T 31 S R 8 W S 1 B T (New B.T.)

A live oak, 7 ins. diam., bears N.23°W., 33 lks. dist. marked T 30 S R 8 W S 36 B T (New B.T.)

Thence

North, retracing the line bet. secs. 31 and 36.

Ascend S. slope, through heavy timber and dense undergrowth.

- 0.30 rt. of bluff, 30 ft. high.
- 3.00 Top of spur, slopes E., descend NE. slope.
- 28.20 Creek, 1 lk. wide, course E.
- 30.10 Table Creek, 8 lks. wide, course S.60°E.
- 36.90 Same creek, 8 lks. wide, course SW.
- 39.17 Fall 92 lks. E. of the 1/4 sec. cor., which is a stone, firmly set, marked and witnessed as described by the surveyor general.. Alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec cor., with brass cap marked

1/4
S36 | S31
1918

from which

A yew, 16 ins. diam., bears S.31°E., 50 lks. dist. marked 1/4 S 31 B T (Old B.T.)

A Maple, 6 ins. diam., bears N.87°30'W., 34 lks. dist. marked 1/4 S 36 B T (Old B.T.)