

Retracement and Survey Portion South bdy., T. 30 S., R. 7 W.

CHAINS

from which

A yellow pine, 24 ins. diam., bears N.25°E., 22 lks. dist., marked $\frac{1}{4}$ S 33 B T.

A fir, 5 ins. diam., bears N.44°30'W., 25 lks. dist. marked $\frac{1}{4}$ S 33 B T.

The true course and length of this line is N.89°13'W., 39.37 chs.

Thence

S.88°18'W., surveying the S. bdy. of sec. 33, counting distance from the sec. cor.

Ascend steep E. slope, through heavy timber and dense undergrowth.

41.17 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 4 only, with brass cap marked

$\frac{1}{4}$ S4
1918

from which

A cedar, 16 ins. diam., bears S.70°E., 28 lks. dist. marked $\frac{1}{4}$ S 4 B T.

A yellow pine, 7 ins. diam., bears S.66°30'W., 70 lks. dist., marked $\frac{1}{4}$ S 4 B T.

42.10 Trail, bears N. and S.

53.45 rt. of conglomerate bluffs, leave timber.

55.55 top of bluffs, 175 ft. high.

56.45 Deep rift in rock, course N., ascend.

62.67 Top of rock dome, descend.

67.65 Deep ravine, course S.15°W., ascend solid wall of rock.

74.25 Rock spur, slopes S., descend.

78.05 Ravine, course S., ascend.

78.46 A point South of the $\frac{1}{4}$ cor. bet. secs. 32 and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 32 and 33, with brass cap marked