

## County Surveyor's Record, Douglas County, Oregon

## Retracement Subdivisions, T. 30 S., R. 7 W.

CHAINS

cor, is N.87\*14'E., 39.38 chs.

Land, mountainous.

Soil, shale rocks and rocky loam, 3rd. and 4th rate.

Timber, fir, live oak and madrona.

Undergrowth, live oak, madrona and tan oak.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy.  
of the Tp.

North, retracing the line bet. secs. 33 and 34.

Descend NW. slope, through heavy timber and dense  
undergrowth.

- 1.75 Foot of slope.  
1.90 Trail, bears NE. and SW.  
5.10 Cow Creek, 410 lks. wide, course NE., ascend.  
9.85 Fence, bears N.55\*E., and S.55\*W.  
10.10 Center of S.P.Ry. track on curve, bears N.55\*E., and S.55\*W.  
11.15 Fence, bears N.55\*E., and S.55\*W. ascend steep S. slope.  
18.50 Top of spur, slopes SE., descend steep NE. slope.  
26.75 Polan Creek, 3 lks. wide, course SE. ascend steep SW. slope.  
39.43 Fall 41 lks. W. of the point for  $\frac{1}{4}$  sec. cor. located by  
reference to the bearing trees. At the exact cor. point  
set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$\frac{1}{4}$   
S33|S34  
1918

from which

A madrona, 14 ins. diam., bears N.22\*E., 13 lks. dist.  
marked  $\frac{1}{4}$  S 34 B T (Old B.T.)

A madrona, 12 ins. diam., bears S.30\*W., 29 lks. dist.  
marked  $\frac{1}{4}$  S 33 B T (Old B.T.)

A fir, 14 ins. diam., bears S.16\*30'E., 59 lks. dist.  
marked  $\frac{1}{4}$  S 34 B T (New B.T.)

A fir, 18 ins. diam., bears N.34\*W., 29 lks. dist.  
marked  $\frac{1}{4}$  S 33 B T (New B.T.)