

South Boundary of T. 30 S., R. 8 W.
 As surveyed by William H. Byars, Deputy Surveyor
 Under Contract No. 456, dated July 28, 1882.

CHAINS

From the Corner to Townships 30 & 31, South, Ranges 7 & 8
 West, I run

West on a Random Line bet. said Townships.

Va. 18*45' East.

I set temp. half-mile and mile corners at each 40. and
 80. chs., and find the Tp. line to be 6 mi. 8 chs.
 and 10 lks. long, and the falling to be 12 chs. and
 75 lks. North of the Cor. to Tps. 30 & 31 S., Rs. 8 & 9
 West. The correction for the True Line will therefore
 be $2.12\frac{1}{2}$ chs. South per mile, and its course will be

N.88*29' East.

September 25, 26, 27, 1882

From the Cor. to Tps. 30 & 31 S. Rs. 8 & 9 W., which is
 a post, 4 ins. sq., firmly set in the ground, and
 marked T 30 S S 31 on the NE. face, R 8 W S 6 on the
 SE., T 31 S S 1 on the SW., and R 9 W S 36 on the NW.,
 and from which

A Fir, 12 ins. diam., bears N.2*E., 43 lks. dist.

Marked T 30 S R 8 W S 31 B T

A Fir, 30 ins. diam., bears S.40*E., 57 lks. dist.

Marked T 31 S R 8 W S 6 B T

A Fir, 15 ins. diam., bears S.75*W., 38 lks. dist.

Marked T 30 S R 9 W S 1 B T

A Fir, 10 ins. diam., bears N.63*W., 25 lks. dist.

Marked T 30 S R 9 W S 36 B T

Thence I run

North 88*29' East on a True Line bet. Secs. 6 & 31.

Va. 19* East.

28.00 A Creek, 2 lks. wide, course N.

32.00 Top of Hill, course N. & S. Descend.

48.10 Set a Fir post four feet long, 4 ins. sq., in the ground
 for the $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on the North side, and
 from which