

Subdivisions of T. 30 S., R. 8 W.

CHAINS	<p>A Fir, 16 ins. diam bears S.26*E., 11 lks, dist. Marked $\frac{1}{4}$ S B T</p>
79.34	<p>The Corner to Secs. 26, 27, 34 & 35. Land; first part mountainous, last part rolling. Timber: Densely covered with forest. Chiefly fir, with some cedar, laurel and pine. Undergrowth: Same kinds of wood. Soil, 2d rate. October 24th, 1882.</p> <hr/> <p>North between Secs. 26 & 27. Var. 19* East. Moderate Ascent along East slope.</p>
20.00	<p>Top of Ridge, course N.30*E. Thence along West slope.</p>
40.00	<p>Set a sand stone 16x14x8 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which A Fir, 12 ins. diam., bears N.75*W., 6 lks. dist. Marked $\frac{1}{4}$ S B T A Laurel, 11 ins. diam., bears S.20*E., 21 lks. dist. Marked $\frac{1}{4}$ S B T Begin Steep Ascent.</p>
67.50	<p>Top of high Ridge, course NW.</p>
80.00	<p>Set a Chincapin post 4 ft. long, 4 ins. sq., 24 ins. in the ground for the Corner to Secs. 22, 23, 26 & 27, marked T 30 S R 8 W S 23 on NE., S 26 on SE., S 27 on SW., and S 22 on NW. faces, with 2 notches on S. & E. edges, from which A Fir, 16 ins. diam., bears N.63*E., 37 lks. dist. Marked T 30 S R 8 W S 23 B T A Fir, 15 ins. diam., bears S.57*E., 21 lks. dist. Marked T 30 S R 8 W S 26 B T A Fir, 5 ins. diam., bears S.61*W., 22 lks. dist. Marked T 30 S R 8 W S 27 B T A Fir, 18 ins. diam., bears N.26*W., 25 lks. dist. Marked T 30 S R 8 W S 22 B T</p>