Subdivisions of T. 30 S., R 9 W., W.M.

CHAINS		
32.00	Offset east 100 lks. to avoid rocks.	+200
32.30	Offset back to line.	+60
35.00	Summit of ridge, course NE and SW.	+125
39.00	Branch, 1 lk. wide, course W.	-50
40.00	Set ¼ sec. post, from which	+20
	A Fir, 40 ins. diam., bears S.65*E., 19 lks. dist.	
	A Fir, 20 ins. diam., bears S.53*W., 32 lks. dist.	
63.10	Branch, 1 lk. wide, course SE.	+100
80.00	Set post, cor. secs. 3, 4, 9 and 10, from which	+125
	A Fir, 36 ins. diam., bears N.56*E., 32 lks. dist.	
	A Fir, 30 ins. diam., bears N. 14*W., 38 lks.dist.	
	A Fir, 10 ins. diam., bears S.75*E., 41 lks. dist.	
	A Fir, 20 ins. diam., bears S.20*W., 35 lks. dist.	
	Surface very uneven.	
	Soil 3rd rate.	
	Timber, fir, cedar, live oak, etc.	
	East on random bet. secs. 3 and 10.	
	Va. 19*E.	
40.00	Set temp. ¼ sec. post.	
79.63	Intersect N and S line, 33 lks. N of post.	
	N.89*46'W., on true line bet. secs. 3 and 10.	
6.00	Enter thick timber, course N and S.	-125
8.00	Branch, 2 lks. wide, course SW.	-40
26.60	Branch, 1 lk. wide, course SE.	+150
39.81½	Set ¼ sec. post, from which	+60
	A Laurel, 12 ins. diam., bears N.8*E., 51 lks. dist.	
	A Laurel, 16 ins. diam. bears S.67*W., 17 lks. dist.	
52.00	Leave thick timber.	+100
53.50	Summit of ridge, course N and S.	+75
70.00	Enter thick timber, course N and S.	-125
73.45	Branch, 2 lks. wide, course S.	-60
79.63	To cor.	+50
	Surface, soil, timber, etc., as last noted.	