

County Surveyor's Record, Douglas County, Oregon

Extracts from Subdivisions of T. 30 S., R 10 W., W.M.

CHAINS

From temp. stake, the $\frac{1}{4}$ sec. cor. bears W, 3 lks. dist.,
I destroy the marks on the $\frac{1}{4}$ sec. tree cor. and also
the marks on the bearing trees. From the temp stake,
I run north.

40.00 I set the $\frac{1}{4}$ sec. cor., 3 lks. west of my line to the
blazed line which cor. is a stone, 15x10x5 ins., 10 ins.
in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from
which

A Fir, 48 ins. diam., bears N.50 $\frac{1}{2}$ *W., 46 lks. dist.,
marked $\frac{1}{4}$ S B T.

A Cedar, 11 ins. diam., bears N.54*E., 61 $\frac{1}{2}$ lks.
dist., marked $\frac{1}{4}$ S B T.

75.85 The cor. to secs. 19, 24, 25 and 30, 6 lks. west of my
line. I destroy this post and also the marks on three
of the witness trees which I find here. Thence I run
north to

80.00 Set cor. to secs. 19, 24, 25 and 30, 6 lks. west of my
line and on the blazed line which cor. is a stone
24x10x8 ins., 18 ins. in the ground marked with 2
notches on S and 4 notches on N edges, from which

A Fir, 34 ins. diam., bears N.27*E., 18 $\frac{1}{2}$ lks. dist.,
marked T 30 S R 9 W S 19 B T.

A Fir, 30 ins. diam., bears S.51 $\frac{1}{4}$ *E., 47 lks. dist.,
marked T 30 S R 9 W S 30 B T.

A Fir, 32 ins. diam., bears S.22*W., 33 $\frac{1}{2}$ lks. dist.,
marked T 30 S R 10 W S 25 B T.

A Fir, 14 ins. diam., bears N.52 $\frac{1}{2}$ *W., 30 lks. dist.,
marked T 30 S R 10 W S 24 B T.

Land mountainous and broken, 80.00 chs.

Soil stony and rocky, 4th rate.

Heavily timbered with fir, cedar, maple, dogwood, laurel
and yew, 70.00 chs.

Dense undergrowth of vinemaple, fir, cedar, hemlock,
rhododendron, huckleberry, myrtle, maple, thimbleberry
and sallah, 80.00 chs.

July 18, 1893