

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T 30 S., R 9 W., W.M.

CHAINS

A Fir, 5 ins. diam., bears N.31*E., 14 lks. dist.,
marked T 30 S R 9 W S 23 B T.

A Fir, 10 ins. diam., bears S.89*E., 21 lks. dist.,
marked T 30 S R 9 W S 26 B T.

A Fir, 6 ins. diam., bears S.5*W., 6 lks. dist.,
marked T 30 S R 9 W S 27 B T.

A Fir, 12 ins. diam., bears N.60*W., 30 lks. dist.,
marked T 30 S R 9 W S 22 B T.

The two last trees were marked in the bark. I mark them
in the wood.

Thence I run

S.0*1'E., on a true line bet. secs. 26 and 27.

Va. 19*15'E., at 4:00 P.M.

	Descend.	-40
1.35	A stream, 3 lks. wide, course SE., ascend.	+20
1.80	Descend.	-40
4.35	Stream, 5 lks. wide, 3 lks. E of line, ascend	+25
5.60	Descend	-25
6.65	Same stream, 5 lks. wide, course NE, ascend.	+500
7.35	A stream, 1 lk. wide, course N.20*W.	
20.40	A stream, 1 lk. wide, course NE.	
24.69	A Fir, 34 ins. diam., on line marked with 2 notches on N and S sides.	
26.00	A dry ravine, course NE and SW.	
33.00	Descend.	-30
34.40	A dry ravine, course E and W., ascend.	+80
39.40	Top of ridge, course NW and SE., descend.	-500
40.27	Set a stone, 18x16x12 ins., 13 ins. in the ground for $\frac{1}{2}$ sec. cor. marked $\frac{1}{2}$ on W face, from which A Fir, 8 ins. diam., bears N.48 $\frac{1}{2}$ *E., 57 lks. dist., marked $\frac{1}{2}$ S B T. A Fir, 10 ins. diam., bears N.71 $\frac{1}{2}$ *W., 94 $\frac{1}{2}$ lks. dist., marked $\frac{1}{2}$ S BT.	