

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R 9 W., W.M.

CHAINS		
20.25	A Fir, 26 ins. diam., on line, marked with 2 notches on N and S sides.	
22.20	Top of sharp ridge course E and W., descend.	-175
28.10	A stream, 4 lks. wide, course SE., ascend.	+300
35.82	A Fir, 36 ins. diam., on line marked with 2 notches on N and S sides.	
40.00	A Fir, tree, 40 ins. diam., which I mark $\frac{1}{2}$ S on W side for $\frac{1}{2}$ sec. cor., from which A Fir, 36 ins. diam., bears S.54*E., 24 lks. dist., marked $\frac{1}{2}$ S B T. A Fir, 40 ins. diam., bears S.6*W., 118 lks. dist., marked $\frac{1}{2}$ S B T.	
47.75	Descend.	-30
50.00	Ascend.	+30
52.00	Descend.	-40
53.75	Ascend.	+40
59.00	Eden trail, course E and W., on Mt. ridge, descend.	-500
69.58	A Fir, 34 ins. diam., on line marked with 2 notches on N and S sides.	
76.17	A Fir, 4 ft. diam., on line marked with 2 notches on N and S sides.	
80.00	Set a stone, 16x14x14 ins., 12 ins. in the ground for cor. to secs. 21, 22, 27 and 28, marked with 2 notches on S and 3 notches on E edges, from which A W Fir, 20 ins. diam., bears N.32*E., 21 $\frac{1}{2}$ lks. dist., marked T 30 S R 9 W S 22 B T. A W Fir, 22 ins. diam., bears S.35 $\frac{1}{2}$ *E., 46 $\frac{1}{2}$ lks. dist., marked T 30 S R 9 W S 27 B T. A W Fir, 12 ins. diam., bears S.46 $\frac{3}{4}$ *W., 20 $\frac{1}{2}$ lks. dist., marked T 30 S R 9 W S 28 B T. A Hemlock, 11 ins. diam., bears N.26*W., 73 $\frac{3}{4}$ lks. dist., marked T 30 S R 9 W S 21 B T.	
	Land mountainous, 80.00 chs.	
	Soil 3rd rate.	
	Heavily timbered with fir, cedar, hemlock, maple, chinquapin and yew, 80.00 chs.	