

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R 9 W., W.M.

CHAINS	From the cor. to secs. 4, 5, 32 and 33, on the south boundary of the township.	
	Thence I run N.0*2'W., bet. secs. 32 and 33. Va. 19*E., at 8 A.M.	
	Ascend.	+50
2.16	A Fir, 36 ins. diam., on line marked with 2 notches on N and S sides.	
4.50	Top of ridge, course NW and SE., descend.	-175
7.28	A Fir, 4 ft. diam., on line marked with 2 notches on N and S sides.	
16.11	A stream, 5 lks. wide, course SE., ascend.	+200
27.50	Top of ridge, course E and W., turns NE 2 chs. E., descend	-175
35.00	A Fir, 4 ft. diam., on line marked with 2 notches on N and S sides.	
38.00	A stream, 1 lk. wide, course NE.	
40.00	Set a stone, 14x8x8 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face, from which A Fir, 14 ins. diam., bears N.19 $\frac{3}{4}$ *E., 27 $\frac{3}{4}$ lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 21 ins. diam., bears N.18*W., 41 lks. dist., marked $\frac{1}{4}$ S B T.	
42.42	A Fir, 5 ft. diam., on line, marked with 2 notches on N and S sides.	
43.30	A stream, 3 lks. wide, course E., ascend.	+500
68.00	A perpendicular bluff. To avoid which, I offset N.89*58'B 1.64 chs. Thence N.0*2'W., on offset line.	
71.50	I offset S.89*58'W., 1.64 chs. to line, on top of Mt. ridge and trail to Eden, course E and W and descend.	-125
80.00	Set a stone, 16x12x10 ins., 12 ins. in the ground for cor. to secs. 28, 29, 32 and 33, marked with 1 notch on S and 4 notches on E edges, from which A Fir, 17 ins. diam., bears N.18 $\frac{3}{4}$ *E., 49 lks. dist., marked T 30 S R 9 W S 28 B T.	