

County Surveyor's Record, Douglas County, Oregon

7457

West Boundary of Fractional T. 31 S., R. 1 W.,
As surveyed by Dennis Hathorn, Deputy Surveyor,
Under his Contract No. 73, dated June 8th, 1857.

CHAINS			
	South, on W. Bdy. sec. 6.		
40.00	Set 1/4 sec. post, from which	Va. 19*30'E.	-300
	An oak, 18 ins. diam., bears N.60*W., 23 lks. dist.		
	An oak, 20 ins. diam., bears S.80*E., 15 lks. dist.		
40.00	Built stone mound.		
59.00	Branch, 2 lks. wide, course W.		-100
60.00	Branch, 2 lks. wide, course W.		level
80.00	Set post, cor. secs. 6, 7, 1 and 12, from which		- 50
	An oak, 10 ins. diam., bears N.14*W., 100 lks. dist.		
	An oak, 12 ins. diam., bears N.28*E., 36 lks. dist.		
	An oak, 9 ins. diam., bears S.18*W., 79 lks. dist.		
	A pine, 24 ins. diam., bears S.68*E., 49 lks. dist.		
	Land, high and hilly; oak and pine openings.		
	Soil, 2nd rate.		
	South, on W. bdy. Sec. 7.		
40.00	Set 1/4 sec. post, from which	Va. 19*E.	-100
	A fir, 12 ins. diam., bears N.12*W., 35 lks. dist.		
	A fir, 12 ins. diam., bears N.57*E., 31 lks. dist.		
66.14	Table rock trail, course NW. and SE.		-300
80.00	Set post, cor. secs. 12, 13, 7 and 18, from which		- 50
	An oak, 12 ins. diam., bears N.12* W., 16 lks. dist.		
	An oak, 15 ins. diam., bears N.17*E., 75 lks. dist.		
	An oak, 12 ins. diam., bears S.57*E., 87 lks. dist.		
	A pine, 36 ins. diam., bears S.7*W., 110 lks. dist.		
	Land, about the same as last mile.		
	South, on W. bdy. sec. 18.		
10.50	A rock, about 10 ft. high. Offset W. 25 lks. to avoid same.	Va. 18*30'E.	10
11.60	Offset E. to line.		
34.33	Ascend perpendicular rocks about 20 ft. high.		50
40.00	Set 1/4 sec. post, from which		+10
	A pine, 36 ins. diam., bears N.15*W., 31 lks..dist.		