

County Surveyor's Record, Douglas County, Oregon

X

Portion of North Boundary of T. 32 S., R. 1 W., as Surveyed by Rufus S. Moore, Deputy Surveyor, Under Contract No. 475, dated July 3, 1883.

CHAINS	
	<p>From the old cor. to secs, 2, 3, 34 and 35, on the N. bdy. of the T., which is a post 4 ins. sq., rotten and decayed, but still standing, with marks almost obliterated, from which,</p> <p>A fir, 20 ins. diam., bears S.70*W., 32 lks. dist., marked T 32 S R 1 W S 3 B T.</p> <p>A fir, 24 ins. diam., bears S.12*E., 55 lks. dist., marked T 32 S R 1 W S 2 B T.</p> <p>I run East, on a true line on S. bdy. of sec. 35.</p> <p style="text-align: right;">Va. 20*E.</p>
26.50	Creek, 8 lks. wide, runs NW. about 150 ft. below sec. cor., and ascend.
40.00	Set a basalt stone, 18x12x8 ins. 12 ins. in the ground for 1/4 sec. cor. about 300 ft. above creek, marked 1/4 on W. face, from which,
	<p>A fir, 14 ins. diam., bears N.67*E., 24 lks. dist., marked 1/4 S B T.</p> <p>A fir, 6 ins. diam., bears S.45*E., 13 lks. dist., marked 1/4 S B T.</p>
65.60	Ravine, course SW. about 100 ft. below 1/4 sec. cor. and ascend.
80.00	Set a basalt stone, 18x12x6 ins. 12 ins. in the ground, for the cor. to secs. 35 and 36, about 500 ft. above 1/4 sec. cor. marked with 1 notch on E. and 5 notches on W. edges, from which
	<p>A fir, 24 ins. diam., bears N.40*E., 7 lks. dist. marked T 31 S R 1 W S 36 B T.</p> <p>A fir, 26 ins. diam., bears N.36*W., 46 lks. dist., marked T 31 S R 1 W S 35 B T.</p>