

County Surveyor's Record, Douglas County, Oregon

Resurvey of North Bdy. of T. 32 S., R. 1 W.

CHAINS

A fir, 15 ins. diam., bears S.10*W., 111 lks. dist.,
mkd. T 32 S R 1 W S 2 B T.

A fir, 10 ins. diam., bears S.10*E., 103 lks. dist.,
mkd. T 32 S R 1 W S 1 B T.

Land, high and mountainous.

Soil, 3rd rate.

Densely covered with forests of fir and cedar, 75.50 chs.

Thick undergrowth of fir, matherone, arrowwood and chin-
quapin, 75.50 chs.

Brushy glade, 4.50 chs.

West, on a true line on N. bdy. of sec. 2.

Va. 20*15'E.

- 3.50 Leave glade and enter timber, bears N.80*E., and SW.
- 7.00 Commence descending ridge, bears N.80*W.
- 31.60 Small ravine, course NW.
- 37.00 The cor. to secs. 35 and 36, established by me in running East, at a point about 500 ft. below point of descending ridge, which is a basalt stone, 18x12x6 ins. 12 ins. in the ground, mkd. with 1 notch on E. and 5 notches on W. edges.
- from which
- A fir, 24 ins. diam., bears N.40*E., 7 lks. dist.,
mkd. T 31 S R 1 W S 36 B T.
- A fir, 26 ins. diam., bears N.36*W., 46 lks. dist.,
mkd. T 31 S R 1 W S 35 B T.
- A fir, 30 ins. diam., bears S.23*W., 22 lks. dist.,
mkd. T 32 S R 1 W S 2 B T.
- 51.40 Small ravine, course SW.
- 77.00 To the 1/4 sec, cor. on S. bdy. of sec. 35 at a point about 500 ft. below last sec. cor. established by me in running E. which is a basalt stone, 18x12x8 ins. 12 ins. in the ground, mkd. 1/4 on N. face.