

27

Dependent Resurvey of Willamette Meridian
Through T. 31 S.

CHAINS

North, on a true line, on E. bdy. of sec. 36.

Over mountainous land, through heavy timber and dense undergrowth.

9.62 40.00 chs. northing from the cor. of Tps. 31 and 32 S., R. 1 E., only.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 31 only, with brass cap mkd.

1/4 S 31
1923

from which

A fir, 16 ins. diam., bears N.4*E., 100 lks. dist., mkd. 1/4 S 31 B T.

A fir, 18 ins. diam., bears S.56*E., 54 lks. dist., mkd. 1/4 S 31 B T.

Asc. 70 ft. to

21.77 Ridge, bears NE. and SW., desc. 393 ft. to 1/4 sec. cor., over NE. slope.

34.74 Trail, bears NW. and SE.

40.00 The 1/4 sec. cor. established for secs. 31 and 36, which is a basalt stone, firmly set, 4x10x6 ins. above ground, mkd. 1/4 on W. face; from which

A fir, 30 ins. diam., bears N.37*E., 49 lks. dist., mkd. 1/4 S 31 B T. (Old B T.)

A fir, 30 ins. diam., bears S.55*W., 33 lks. dist., mkd. 1/4 S 36 B T. (Old B T.)

I now change this cor. to refer to sec. 36 only, and obliterate the marks on the bearing tree referring to sec. 31.

Re-mark the stone

1/4 S 36 on W. face; from which

A fir, 10 ins. diam., bears N.87*W., 36 lks. dist., mkd. 1/4 S 36 B T. (New B T.)