

Dependent Resurvey of Willamette Meridian
through T. 31 S.

CHAINS

North, on E. bdy. of sec. 25.

Over mountainous land, through heavy timber and dense undergrowth.

Desc. 36 ft. over NE. slope.

2.57 Spring branch, 3 lks. wide, course SE.; asc. 77 ft. over SW. slope to

9.62 Set an iron post, 3 ft. long 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 30 only, with brass cap marked

1/4 S30

1923

from which

A fir, 16 ins. diam., bears S.56*E., 141 lks.

dist., mkd. 1/4 S 30 B T.

A fir, 34 ins. diam., bears N.14*E., 45 lks.

dist., mkd. 1/4 S 30 B T.

Asc. 336 ft. to

40.00 The 1/4 sec. cor. established for secs. 25 and 30, which is a basalt stone, firmly set, 4x8x8 ins. above ground, mkd. 1/4 on W. face; from which

A fir, 40 ins. diam., bears S.55*E., 27 lks.

dist., mkd. 1/4 S 30 B T. (Old B T.)

A fir, 40 ins. diam., bears S.75*W., 15 lks.

dist., mkd. 1/4 S 25 B T. (Old B T.)

I now change this cor. to refer to sec. 25 only, and obliterate the marks on the bearing tree referring to sec. 30.

Re-mark the stone

1/4 S 25 on W. face; from which

A fir, 18 ins. diam., bears N.59*W., 37 lks.

dist., mkd. 1/4 S 25 B T. (New B T.)

40.25 Divide bet. Rogue River and Umpqua River, bears NW. and SE.