

Dependent Resurvey of Willamette Meridian
through T. 31 S.

CHAINS

Forest Service telephone line and trail, bears NW. and SE.
Desc. 122 ft. over NE. slope, to

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 19 and 30 only, with
brass cap marked

T31S	T31S
	S19
R1W	S30
S25	R1E
	1923

from which

A hemlock, 24 ins. diam., bears N.35*E., 41 lks.
dist., mkd. T 31 S R 1 E S 19 B T.

A yew, 12 ins. diam., bears S.58*E., 20 lks.
dist., mkd. T 31 S R 1 E S 30 B T.

Desc. 216 ft. to

66.85 Dry creek bed, 10 lks. wide, course NW.; asc. 206 ft.
over SW. slope.

80.00 The cor. of secs. 24 and 25 only, which is a basalt
stone, firmly set, 4x10x6 ins. above ground, marked
with 4 notches on N., and 2 notches on S. edge; from
which

A fir, 30 ins. diam., bears S.75*W., 34 lks.
dist., mkd. T 31 S R 1 W S 25 B T. (Old B T.)

A fir, 12 ins. diam., bears N.50*W., 48 lks.
dist., mkd. T 31 S R 1 W S 24 B T. (Old B T.)

Re-mark the stone

S 25 on SW., and

S 24 on NW. face.

Land, mountainous.

Soil, rocky; 4th. rate.

Timber, fir and cedar.

Undergrowth, vine maple and hazel.