

53

Dependent Resurvey of Willamette Meridian
through T. 31 S.,

CHAINS

North, on E. bdy. of sec. 24.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 43 ft. over SW. slope, to

9.62 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 19 only, with brass cap marked

1/4 S 19
1923

from which

A fir, 30 ins. diam., bears N.51*E., 24 lks. dist., mkd. 1/4 S 19 B T.

A fir, 25 ins. diam., bears S.46*E., 31 lks. dist., mkd. 1/4 S 19 B T.

15.00 Spur, slopes NW.; desc. 43 ft. over NE. slope.

40.00 The 1/4 sec. cor. established for secs. 19 and 24, which is a basalt stone, firmly set, 4x10x6 ins. above ground, mkd. 1/4 on W. face; from which

A fir, 10 ins. diam., bears N.25*E., 26 lks. dist., mkd. 1/4 S 19 B T. (Old B T.)

The old bearing tree in sec. 24 is dead and fallen.

I now change this cor. to refer to sec. 24 only, and obliterate the marks on the bearing tree referring to sec. 19.

Re-mark the stone

1/4 S 24 on W. face; from which

A fir, 30 ins. diam., bears S.69*W., 73 lks. dist., mkd. 1/4 S 24 B T. (New B T.)

A fir, 6 ins. diam., bears N.82*W., 23 lks. dist., mkd. 1/4 S 24 B T. (New B T.)

Desc. 292 ft. to

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 18 and 19, only, with brass