

53

Dependent Resurvey of Willamette Meridian
through T. 31 S.,

CHAINS

9.62 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 18 only, with brass cap marked

1/4 S 18
1923

from which

A hemlock, 5 ins. diam., bears N.43*E., 18 lks. dist., mkd. 1/4 S 18 B T.

A chinquapin, 5 ins. diam., bears S.71*E., 37 lks. dist., mkd. 1/4 S 18 B T.

10.25 Recross same creek, 4 lks. wide, course NE.

12.10 Recross same creek, 4 lks. wide, course W., 209 ft. below sec. cor.

Asc. 320 ft. over SW. slope.

32.50 Spur, slopes NW.; desc. 140 ft. over NE. slope.

40.00 The 1/4 sec. cor. established for secs. 13 and 18, which is a basalt stone, firmly set, 5x10x5 ins. above ground, marked 1/4 on W. face; from which

A cedar, 14 ins. diam., bears S.70*E., 23 lks. dist., mkd. 1/4 S 18 B T. (Old B T.)

The old bearing tree in sec. 13 is dead.

I now change this cor. to refer to sec. 13 only, and obliterate the marks on the bearing tree referring to sec. 18.

Re-mark the stone

1/4 S 13 on W. face; from which

A fir, 40 ins. diam., bears S.22*W., 169 lks. dist., mkd. 1/4 S 13 B T. (New B T.)

A fir, 48 ins. diam., bears N.2*W., 177 lks. dist., mkd. 1/4 S 13 B T. (New B T.)

Desc. 91 ft. to

47.50 Brook, 1 lk. wide, course W.; asc. 17 ft. to