

Dependent Resurvey of Willamette Meridian
through T. 31 S.,

CHAINS

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7 and 18 only, with brass cap marked

T31S	T31S
	S7
R1W	S18
S13	R1E
	1923

from which

A fir, 40 ins. diam., bears N.53*E., 11 lks.
dist., mkd. T 31 S R 1 E S 7 B T.

A fir, 40 ins. diam., bears S.66*E., 84 lks.
dist., mkd. T 31 S R 1 E S 18 B T.

Asc. 115 ft. to

80.00 The cor. of secs. 12 and 13 only, which is a basalt stone firmly set, 5x15x6 ins. above ground, marked with 2 notches on N. and 4 notches on S. edge; from which

A fir, 12 ins. diam., bears N.71*W., 21 lks.
dist., mkd. T 31 S R 1 W S 12 B T. (Old B T.)

The old bearing tree in sec. 13 is dead and fallen.

Re-mark stone

S13 on SW. and

S12 on NW. face; from which

A cedar, 18 ins. diam., bears S.30*W., 37 lks.
dist., mkd. T 31 S R 1 W S 13 B T. (New B T.)

Land, mountainous.

Soil, rocky, 4th. rate.

Timber, fir and cedar.

Undergrowth, vine maple and hazel.

North, on E. bdy. of Sec. 12.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 50 ft. along W. slope.