

Dependent Resurvey of Willamette Meridian
through T. 31 S.,

CHAINS

- 9.62 Set a basalt stone, 20x15x8 ins., 15 ins. in the ground, for 1/4 sec. cor. of sec. 7 only, marked 1/4 S 7 on E. face; from which
- A fir, 28 ins. diam., bears N.23*E., 65 lks. dist., mkd. 1/4 S 7 B T.
- A fir, 36 ins. diam., bears S.26*E., 43 lks. dist., mkd. 1/4 S 7 B T.
- No iron post available.
- 12.00 Top of ridge, bears NW. and SE.; desc. over NE. slope, 759 ft. to 1/4 sec. cor.
- 34.60 Bluff, 35 ft. high, faces N.
- 40.00 The 1/4 sec. cor. established for secs. 7 and 12, which is a basalt stone, firmly set, 5x12x5 ins. above ground, mkd. 1/4 on W. face; from which
- A fir, 10 ins. diam., bears N.60*E., 39 lks. dist., mkd. 1/4 S 7 B T (Old B T.)
- A fir, 12 ins. diam., bears N.84*W., 62 lks. dist., mkd. 1/4 S 12 B T. (Old B.T.)
- I now change this cor. to refer to sec. 12 only, and obliterate the marks on the bearing tree referring to sec. 7.
- Re-mark the stone.
- 1/4 S 12 on W. face; from which
- A maple, 14 ins. diam., bears S.16*W., 56 lks. dist., mkd. 1/4 S 12 B T. (New B T.)
- Desc. 105 ft. to
- 43.60 Beaver Creek, 20 lks. wide, course NW.; asc. 130 ft. over S. slope.
- 49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 6 and 7 only, with brass cap marked

T31S	T31S
	S6
R1W	_____
	S7
S12	R1E
1923	