

Dependent Resurvey of Willamette Meridian
through T. 31 S.,

CHAINS

A cedar, 20 ins. diam., bears S.55*W., 46 lks. dist.,
mkd. 1/4 S 6 B T.

9.94 Spring branch, 3 lks. wide, course SW.; asc. 533 ft.
over S. slope.

14.36 Trail, from Whiskey Camp to Beaver Lake, bears E. and W.

38.20 Top of ridge, bears E. and W.; desc. 27 ft. over NW.
slope.

40.00 The 1/4 sec. cor. established for secs. 1 and 6, which is
a basalt stone, firmly set, 5x12x6 ins. above ground,
mkd. 1/4 on W. face; from which

A fir, 50 ins. diam., bears N.70*E., 22 lks. dist.,
mkd. 1/4 S 6 B T. (Old B T.)

A fir, 24 ins. diam., bears S.30*W., 79 lks. dist.,
mkd. 1/4 S 1 B T. (Old B T.)

I now change this cor. to refer to sec. 1 only, and ob-
literate the marks on the bearing tree referring to
sec. 6.

Remark the stone

1/4 S 1 on W. face; from which

A fir, 64 ins. diam., bears N.40*W., 19 lks. dist.,
mkd. 1/4 S 1 B T. (New B T.)

Desc. 228 ft. to

49.62 Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in
the ground, for cor. of Tps. 30 and 31 S., R.1 E.
only, with brass cap marked

T31S	T30S
R1W	R1E
	S31
S1	S6
	T31S
	1923

from which

A black oak, 7 ins. diam., bears N.84*E., 60 lks.
dist., mkd. T 30 S R 1 E S 31 B T.

A madrona, 16 ins. diam., bears S.72*E., 34 lks.
dist., mkd. T 31 S R 1 E S 6 B T.