

Dependent Resurvey of Portion of South Boundary
of T. 31 S., R. 1 W.

CHAINS

A fir, 6 ins. diam., bears N.5*W., 29 lks. dist.,
mkd. T 31 S R 1 W S 35 B T. (Old B.T.)

The bearing tree in sec. 2 is dead and fallen.

I obliterate the marks on the bearing tree referring to
sec. 35, and in place of the decayed fir post

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 2 and 3, T. 32 S., R. 1
W. only, with brass cap marked

T31S R1W
S35

S3 S2
T32S R1W
1923

From which

A fir, 12 ins. diam., bears S.55*E., 47 lks. dist.,
mkd. T 32 S R 1 W S 2 B T. (New B T.)

39.44 The old 1/4 sec. cor., which is a basalt stone, firmly
set, 6x12x8 ins. above ground, marked 1/4 on N. face;
from which

A fir, 14 ins. diam., bears N.67*E., 24 lks. dist.,
mkd. 1/4 S B T. (Old B T.)

The old bearing tree SE. of cor. is dead.

I now change this cor. to an angle point; obliterate the
marks on the stone and bearing tree and re-mark the
tree A P and the stone

A P on N. face; from which

A fir, 14 ins. diam., bears S.80*E., 37 lks. dist.,
mkd. A P B T. (New B T.)

Thence

N.89*40'E., continuing measurement.

39.97 Gulch, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for 1/4 sec. cor. of sec. 35 only, with brass
cap marked

1/4 S35

1923