

Dependent Resurvey of Portion Of South Boundary
of T. 31 S., R. 1 W.,

CHAINS

from which

A maple, 10 ins. diam., bears N.42*E., 12 lks. dist.,
mkd. 1/4 S 35 B T.

A fir, 14 ins. diam., bears N.72*W., 35 lks. dist.,
mkd. 1/4 S 35 B T.

64.54 Ravine, course SW.

Asc. 277 ft. to sec. cor.

79.22 The old cor. of secs. 35 and 36, which is a basalt stone,
firmly set, 6x12x6 ins. above ground, marked with 1
notch on E. and 5 notches on W. edge; from which

A fir, 16 ins. diam., bears N.40*E., 7 lks. dist.,
mkd. T 31 S R 1 W S 36 B T. (Old B T.)

A fir, 24 ins. diam., bears N.36*W., 33 lks. dist.,
mkd. T 31 S R 1 W S 35 B T. (Old B T.)

The bearing tree referring to sec. 2 is dead.

I now change this cor. to an angle point; obliterate marks
on bearing trees and re-mark same A P. Re-mark the
stone

A P on N. face.

Thence

East, continuing measurement.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 35 and 36 only, with
brass cap marked

T31S	R1W
S35	S36
S2	
T32S R1W	
1923	

from which

A fir, 28 ins. diam., bears N.72*E., 18 lks. dist.,
mkd. T 31 S R 1 W S 36 B T.

A fir, 36 ins. diam., bears N.20*W., 4 lks. dist.,
mkd. T 31 S R 1 W S 35 B T.