



County Surveyor's Record, Douglas County, Oregon

Retracement of Portion of South Boundary
of T. 30 S., R. 1 W.

| CHAINS | |
|--------|--|
| | From the cor. of secs. 4, 5, 32 and 33. East, retracing bet. secs. 4 and 33. |
| 40.96 | Intersect the old 1/4 sec. cor. |
| 81.29 | Fall 30 lks. N. of the old cor. of secs. 3, 4, 33 and 34. The bearing and length of the west half is East, 40.96 chs., and of the east half mile is S.89*34'E., 40.33 chs. |
| | Thence East, from the sec. cor., bet. secs. 3 and 34. |
| 40.52 | Intersect the old 1/4 sec. cor. |
| 80.93 | Intersect the old cor. of secs. 2, 3, 34 and 35. The bearing and length of the west half ^{mile} is East, 40.52 chs., and of the east half mile is East, 40.41 chs. |
| | Thence East, from the sec. cor., bet. secs. 2 and 35. |
| 40.17 | Fall 26 lks. S. of the old 1/4 sec. cor. |
| 80.18 | Fall 38 lks. S. of the old cor. of secs. 1, 2, 35 and 36. The bearing and length of the west half mile is N.89*38'E., 40.17 chs., and of the east half mile is N.89*50'E., 40.01 chs. |

Dependent Resurvey of Portion of South Boundary
of T. 30 S., R. 1 W.

The cor. of secs. 4, 5, 32 and 33; located by reference to the original bearing trees, From cor. point

A laurel, 12 ins. diam., bears S.74*E., 16 lks. dist.,
mkd. T 31 S R 1 W S 4 B T. (Old B T.)

A fir, 15 ins. diam., bears S.88*W., 14 lks. dist.,
mkd. T 31 S R 1 W S 5 B T. (Old B T.)

A fir, 20 ins. diam., bears N.40*E., 15 lks. dist.,
mkd. T 30 S R 1 W S 33 B T. (Old B T.)

The old bearing tree in sec. 32 is dead and fallen.

At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in