

Dependent Resurvey of Portion of South Boundary
of T. 30 S., R. 1 W.

CHAINS

A fir, 10 ins. diam., bears S.39*W., 55 lks. dist.,
mkd. 1/4 S 4 B T.

40.96 The old 1/4 sec. cor., located by reference to the original
bearing trees. From cor. point

A yew, 20 ins. diam., bears N.10*E., 18 lks. dist.,
mkd. 1/4 S B T. (Old B T.)

A fir, 18 ins. diam., bears S.10*W., 20 lks. dist.,
mkd. 1/4 S B T. (Old B T.)

I now change this cor. to refer to sec. 33 only, and ob-
literate the marks on the bearing tree SW. of cor.

At exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for 1/4 sec. cor of sec. 33 only, with
brass cap marked

1/4 S33

1923

from which

A cedar, 12 ins. diam., bears N.60*W., 19 lks. dist.,
mkd. 1/4 S 33 B T. (New B T.)

Thence

S.89*34'E.

0.41 Creek, 4 lks. wide, course NE.

5.99 Creek, 5 lks. wide, course NE.

7.59 Creek, 3 lks. wide, course NE.

22.23 Creek, 2 lks. wide, course NE.

37.04 Point of intersection of line bet. secs. 3 and 4, de-
termined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for closing cor. of secs. 3 and 4, with
brass cap marked

T30S RLW
S33

S4 S3
T31S RLW
CC
1923