

Dependent Resurvey of Portion of South Boundary
of T. 30 S., R. 1 W.

CHAINS

from which

An oak, 15 ins. diam., bears N.58*E., 123 lks. dist.,
mkd. 1/4 S 34 B T.

A fir, 24 ins. diam., bears N.13*W., 267 lks. dist.,
mkd. 1/4 S 34 B T.

43.53 Leave rocky prairie, bears NW. and SE.

44.03 Draw, course NE.; ^{ascend} /45 ft. over NW. slope.

45.71 Spur, slopes NE.; desc. 166 ft. over E. slope.

56.24 Beaver Creek, 25 lks. wide, course NW.; asc. 236 ft. to
sec. cor., over SW. slope.

60.93 Beaver Creek trail, bears NW. and SE.

77.79 Point of intersection of line bet. secs. 2 and 3, de-
termined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for closing cor. of secs. 2 and 3, with
brass cap marked

T30S R1W	
S34	
<hr/>	
S3	S2
T31S	R1W
CC	
1923	

from which

A fir, 40 ins. diam., bears S.24*E., 24 lks. dist.,
mkd. T 31 S R 1 W S 2 C C B T.

A fir, 38 ins. diam., bears S.27*W., 14 lks. dist.,
mkd. T 31 S R 1 W S 3 C C B T.

80.93 The old cor. of secs. 2, 3, 34 and 35, located by reference
to the original bearing trees. From cor. point

An oak, 14 ins. diam., bears N.45*E., 51 lks. dist.,
mkd. T 30 S R 1 W S 35 B T. (Old B T.)

A fir, 18 ins. diam., bears S.40*E., 6 lks. dist.,
mkd. T 31 S R 1 W S 2 B T. (Old B T.)