

County Surveyor's Record, Douglas County, Oregon

7533

77 X

Retracement of Portion of Subdivisional Lines in T. 31 S., R. 1. W.

CHAINS	
	Thence
	S.89°45'W., from the sec. cor., retracing bet. secs. 27 and 34.
40.75	Fall 9 lks. N. of the 1/4 sec. cor.
81.79	Fall 15 lks. N. of the cor. of secs. 27, 28, 33, and 34.
	The bearing and length of the east half mile is S.89°37'W., 40.75 chs., and of the west half mile is S.89°40'W., 41.04 chs.
	Thence
	North, from the sec. cor., retracing bet. secs. 27 and 28.
40.25	Fall 8 lks. E. of the 1/4 sec. cor.
80.43	Fall 33 lks. E. of the cor. of secs. 21, 22, 27, and 28.
	The bearing and length of the south half mile is N.0°07'W., 40.25 chs., and of the north half mile is N.0°21'W., 40.18 chs.
	Thence
	North, from the sec. cor., retracing bet. secs. 21 and 22.
40.20	Intersect the 1/4 sec. cor.
80.86	Intersect the cor. of secs. 15, 16, 21 and 22.
	The bearing and length of the south half mile is North, 40.20 chs., and of the north half mile is North, 40.66 chs.
	Thence
	North, from the sec. cor., retracing bet. secs. 15 and 16.
40.00	After diligent search find no evidence of the 1/4 sec. cor.
81.32	Fall 28 lks. W. of the cor. of secs. 9, 10, 15 and 16.
	The bearing and length of this mile is N.0°12'E., 81.32 chs., and proportional length of each half mile is 40.66 chs.
	Thence
	N.89°32'W., from the sec. cor., retracing bet. secs. 9 and 16.
39.74	After diligent search find no evidence of the 1/4 sec. cor.