


Dependent Resurvey of Portion of Subdivisional Lines
in T. 31 S., R. 1 W.

CHAINS

- 7.50 Sled road, bears NW. and SE.
- 8.80 California-Oregon Power Co. transmission line, bears E. and W.
- 34.42 Fence, bears NW. and SE.
- 36.09 Trail, bears NW. and SE.
- 40.02 The point for the 1/4 sec. cor., determined by reference to the original bearing trees, found to agree with the record.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked



from which

- A black oak, 48 ins. diam., bears S.24*W., 73 lks. dist., mkd. 1/4 S 34 B T. (New B T.)
- A black oak, 14 ins. diam., bears S.66*E., 42 lks. dist., mkd. 1/4 S 35 B T. (New B T.)

Note: New witnesses are taken by reason of intervening growth of younger timber, furnishing better witnesses than the original trees, on which the old blazes are badly decayed.

Thence

N.0*20'E.

- 0.84 Leave timber, bears NW. and SE.; ascend.
- 4.74 Fence, bears NW. and SE.; enter field, bears NW. and SE.
- 13.22 Fence, bears E. and W.; leave field, bears E. and W.
- 40.14 The cor. of secs. 26, 27, 34 and 35, located by reference to the original bearing trees, 445 ft. above 1/4 sec. cor.

At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap marked