

81

Dependent Resurvey of Portion of Subdivisional Lines
in T. 31 S., R. 1 W.

CHAINS

A fir, 7 ins. diam., bears N.19*W., 17 lks. dist.,
mkd. 1/4 S 27 B T.

40.75 The point for the 1/4 sec. cor. established for secs. 27
and 34, which I determine by reference to the original
bearing tree.

I now change this cor. to refer to sec. 34 only.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for 1/4 sec. cor. of sec. 34 only, with brass
cap marked

1/4 S34
1923

from which

A fir, 8 ins. diam., bears S.75*E., 52 lks. dist.,
mkd. 1/4 S 34 B T. (New B.T.)

A fir, 10 ins. diam., bears S.36*W., 27 lks. dist.,
mkd. 1/4 S 34 B T. (New B.T.)

A dead oak, 15 ins. diam., bears S.17*E., 139 lks.
dist., mkd. 1/4 S B T. (Old B.T.)

The original bearing tree referring to sec. 27 is
dead and fallen.

Thence

S.89*40'W.

4.08 Fence, bears NE. and SW.

4.24 Trail, bears NE. and SW.

8.44 Trail, bears NW. and SE.

11.60 Trail, bears NW. and SE.

27.00 Trail, bears NE. and SW.

41.04 The cor. of secs. 27, 28, 33 and 34, which is a badly
decayed fir post, with marks indecipherable.

In place of the decayed post

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 27, 28, 33 and 34, with
brass cap marked