

Dependent Resurvey of Portion of Subdivisional Lines  
in T. 31 S., R. 1 W.

CHAINS

- 3.95 Draw, course NW.
- 24.64 Gulch, course SW.
- 32.00 Spur, slopes SW.
- 34.90 Spring branch, 2 lks. wide, course SW.; ascend.
- 40.08 Mid point on W. bdy. of sec. 22, determined as hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 22 only, with brass cap marked

1/4 S22  
|  
1923

from which

A cedar, 16 ins. diam., bears N.21\*E., 65 lks. dist., mkd. 1/4 S 22 B T.

A fir, 34 ins. diam., bears S.10\*E., 12 lks. dist., mkd. 1/4 S 22 B T.

- 40.20 The 1/4 sec. cor., located by record measurement from the original bearing trees. From cor. point

A fir, 34 ins. diam., bears S.10\*E., 24 lks. dist., mkd. 1/4 S B T. (Old B.T.)

A fir, 34 ins. diam., bears N.54\*W., 59 lks. dist., mkd. 1/4 S B T. (Old B.T.)

I now change this cor. to refer to sec. 21 only, and obliterate the marks on the bearing tree referring to sec. 22.

At exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 21 only, with brass cap marked

1/4 S21  
|  
1923

from which