

County Surveyor's Record, Douglas County, Oregon

75

Dependent Resurvey of Portion of Subdivisional Lines
in T. 31 S., R. 1 W.

CHAINS

A fir, 18 ins. diam., bears S.50*W., 30 lks. dist.,
mkd. 1/4 S 21 B T.


Asc. 500 ft. to sec. cor.

47.50 Leave timber; enter prairie, bears E. and W.

77.00 Leave prairie; enter timber, bears NW. and SE.

80.16 Point of intersection of line bet. secs. 15 and 22, de-
termined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for closing cor. of secs. 15 and 22, with
brass cap marked



from which

A fir, 30 ins. diam., bears N.35*E., 33 lks. dist.,
mkd. T 31 S R 1 W S 15 C C B T.

A fir, 36 ins. diam., bears S.55*E., 7 lks. dist.,
mkd. T 31 S R 1 W S 22 C C B T.

80.86 The cor. established for secs. 15, 16, 21 and 22, which
is a badly decayed fir post, with marks still legible;
from which

A fir, 24 ins. diam., bears N.37*E., 40 lks. dist.,
mkd. T 31 S R 1 W S 15 B T. (Old B.T.)

A fir, 15 ins. diam., bears S.80*E., 32 lks. dist.,
mkd. T 31 S R 1 W S 22 B T. (Old B.T.)

A fir, 16 ins. diam., bears S.5*W., 45 lks. dist.,
mkd. T 31 S R 1 W S 21 B T. (New B.T.)

A fir, 40 ins. diam., bears N.45*W., 4 lks. dist.,
mkd. T 31 S R 1 W S 16 B T. (Old B.T.)

The original bearing tree in sec. 21 is dead and
fallen.